



PRODUCT SPECIFICATION SHEET

PHENOL, LIQUEFIED 90% (CARBOLIC ACID, C₆H₅OH)

<u>PROPERTY</u>	<u>TEST METHOD</u>	<u>SPECIFICATION</u>
Appearance	Visual	Clear Liquid–Colorless Solid
Color, Apha	ASTM D-1209	20 Maximum *
% Phenol	ASTM E260/E1510	89.0%-92.0%

*At time of shipment

PHYSICAL PROPERTIES

Melting Point	16° C
Boiling Point	182° C
Non-Volatile Matter	0.05% Maximum
Solubility	Moderately soluble in water (8.4% @ 20°C), alcohol, ether, chloroform, ethyl acetate, toluene, and glycerol

**NOTE: Phenol is shipped as a liquid. Phenol begins to solidify below 16° C.*

EZ Chem LLC ~ 14900 SW 30th Street, Unit #278352 ~ Miramar, FL 33027
Phone 888.828.7099 ~ info@ezchemllc.com

The information herein is to assist customers in determining whether our products are suitable for their applications. Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to contents and suitability. We warrant that our products will meet our written specifications. Nothing herein shall constitute any other warranty express or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. All patent rights are reserved. The exclusive remedy or all proven claims is replacement of our materials and in no event shall we be liable for special, incidental or consequential damages.